

Special Tec T3410 5W-40

Description

Advanced full synthetic low-friction motor oil for year-round use in numerous vehicles from international manufacturers. Ensures reliable lubrication, minimizes wear and keeps the engine clean. Guarantees excellent performance with extremely low fuel consumption. Ideally suited for engines with start-stop system.

Properties

- outstanding engine cleanliness
- saves fuel and reduces pollutant emissions
- tested for turbochargers and catalytic converters
- excellent wear resistance
- good ageing stability
- outstanding lubrication reliability

Specifications / Approvals

ACEA A3/B4 • API SP

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

API SN • API SN PLUS

Technical data

SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,855 g/cm ³ ASTM D4052
Viscosity at 40 °C	80,5 mm ² /s ASTM D445
Viscosity at 100 °C	13,5 mm ² /s ASTM D445
Viscosity at -35 °C (MRV)	≤ 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	170 ASTM D2270
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-45 °C ASTM D97
Evaporation loss (Noack)	10,0 % ASTM D5800
Flash point	220 °C ASTM D92
Total base number	12,2 mg KOH/g ASTM D2896



Technical data

Sulfate ash	1,0 - 1,6 g/100g ASTM D874
Color number (ASTM)	L 3,5 ASTM D1500

Areas of application

For gasoline, diesel and hybrid vehicles.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed

Available pack sizes

1 l Canister plastic	48345 DE-EN-ID-TH
3,5 l Canister plastic	48354 DE-EN-ID-TH
4 l Canister plastic	48346 DE-EN-ID-TH
60 l Black plate barrel	48390 EN
205 l Black plate barrel	48327 EN

Our information is based on thorough research and may be considered reliable, although not legally binding.